

## Speed

Maximum speed: **12.5 mph / 20 km/h**  
Top speed can be set by rider.

## Range

**16-24 miles / 26-39 km** per charge\*

## Payload

Total capacity (rider & cargo): **260 lbs / 118 kg**

Rider: **100-250 lbs / 45-113 kg**

## Power

Two Saphion® lithium-ion battery packs:

**96 Cells, 73.6 VDC, 5.3 Ah** per pack

Built-in charger accepts **100-240 VAC, 50-60 Hz**

Recharge time: **8-10 hrs\*\***

## Interaction

### Segway SmartMotion™

Balances the PT while enabling precise and responsive forward/reverse rider control.

### LeanSteer™

Differentiates turns from bumps.  
Compensates for uneven terrain.  
Zero turning radius.

### Wireless InfoKey™ Controller

Powers PT on/off.  
Enables/disables security and beginner functions.  
Displays battery level, time, date, speed, average speed, odometer, trip odometer.

## Configurations

Individuals	Business	Police & Government
· i2	· i2	· i2
· i2 Commuter	· i2 Cargo	· i2 Police

## Terrain

**Varied:** designed for both indoor & outdoor use

## Operating Temperature

**14° to 122° F / -10° to 50° C\*\*\***

## Size & Weight

Footprint: **19 x 25 in / 48 x 64 cm**

Ground clearance: **3.5 in / 9 cm**

Platform height: **8.5 in / 22 cm**

Weight: **105 lbs / 48 kg**



\* Range may vary depending on factors such as terrain, wind, weight of rider, and weight of cargo.

\*\* Recharge time based on fully discharged battery packs. Charge time for partially charged batteries will be less.

\*\*\* For best performance, store and charge at room temperature.

## Speed

Maximum speed: **12.5 mph / 20 km/h**  
Top speed can be set by rider.

## Range

**10-14 miles / 16-22.5 km** per charge\*

## Payload

Total capacity (rider & cargo): **260 lbs / 118 kg**

Rider: **100-250 lbs / 45-113 kg**

## Power

Two Saphion® lithium-ion battery packs:

**96 Cells, 73.6 VDC, 5.3 Ah** per pack

Built-in charger accepts **100-240 VAC, 50-60 Hz**

Recharge time: **8-10 hrs\*\***

## Interaction

### Segway SmartMotion™

Balances the PT while enabling precise and responsive forward/reverse rider control.

### LeanSteer™

Differentiates turns from bumps.  
Compensates for uneven terrain.  
Zero turning radius.

### Wireless InfoKey™ Controller

Powers PT on/off.  
Enables/disables security and beginner functions.  
Displays battery level, time, date, speed, average speed, odometer, trip odometer.

## Configurations

### Individuals

- x2
- x2 Adventure
- x2 Golf

### Business

- x2
- x2 Golf

### Police & Government

- x2
- x2 Police

## Terrain

**Rugged:** designed outdoor use

## Operating Temperature

**14° to 122° F / -10° to 50° C\*\*\***

## Size & Weight

Footprint: **21 x 30.5 in / 53 x 77 cm**

Ground clearance: **4.5 in / 11 cm**

Platform height: **9.5 in / 24 cm**

Weight: **120 lbs / 54 kg**



\* Range may vary depending on factors such as terrain, wind, weight of rider, and weight of cargo.

\*\* Recharge time based on fully discharged battery packs. Charge time for partially charged batteries will be less.

\*\*\* For best performance, store and charge at room temperature.